Listing of Claims

This listing of claims will replace all prior versions and listings of claims in the application.

- 1. (currently amended) A shaped seal for sealing a power-operated closing device, including an anti-trap guard comprising at least two electrically conductive portions spaced away from each other, whose contact triggers a switching action for activating the <u>a</u> drive assembly of <u>said a</u> closing device, at least one of said portions being electrically conductive <u>and</u> connected to a metallic conductor to reduce the volume resistivity, <u>characterized in that and</u> said metallic conductor is <u>being</u> configured as <u>one of</u> a carrier for securing said shaped seal <u>and/or as and</u> a flange or frame to which said shaped seal is securable.
- 2. (currently amended) The shaped seal as set forth in claim 1, eharacterized in that wherein said carrier contacts said electrically conductive portion.
- 3. (currently amended) The shaped seal as set forth in claim 1, eharacterized in that wherein said carrier is surrounded partly or fully by said electrically conductive portion.
- 4. (currently amended) The shaped seal as set forth in claim 1, characterized in that wherein said carrier is provided with recesses.
- 5. (currently amended) The shaped seal as set forth in claim 1, characterized in that wherein said electrically conductive portion extends up to the outer side of said shaped seal.

- 6. (currently amended) The shaped seal as set forth in claim 5, characterized in that wherein said electrically conductive portion comprises lips or tabs for securing said shaped seal to said flange or to said frame.
- 7. (currently amended) The shaped seal as set forth in claim 1, characterized in that wherein said anti-trap guard portion comprises a hollow chamber in which at least one of said electrically conductive portions is arranged.
- 8. (currently amended) The shaped seal as set forth in claim 7, characterized in that wherein said hollow chamber serves to seal said powered closing device.
- 9. (currently amended) The shaped seal as set forth in claim 1, characterized in that wherein said electrically conductive portion provided separate from said carrier, said flange, or said frame comprises a metallic conductor.